Tel: (508) 842-2224 Fax: (508) 842-3893



34 Fruit St., Shrewsbury, MA 01545

THE FO-700 FLUX OVEN

Stores Submerged Arc Flux by keeping it



FEATURES:

- 700 lb. (318 kg) Flux storage capacity.
- Powerful 4000 watt heating elements. (Uses "low watt density" elements to prevent localized over heating of Flux).
- Total and uniform heating of Flux. (Heating elements extend through the Flux, insuring total heat transfer. Most Flux particles are not more than 2" from a heating element.)
- Temperature range from 175°F to 550°F (79°C to 288°C)
- Accurate temperature control.
- Large thermometer for easy remperature reading (indicates both of and oc).
- High temperature fiberglass insulation for maximum efficiency.
- Removable slag screen.
- Lifting bales and fork lift rails make moving easy.
- Flux valve on front of oven discharges hot Flux quickly and easily into an appropriate container.

SPECIFICATIONS:

- Input power: (4000 watts) 220V/1ph/50-60Hz (19 amps) standard (all other input voltages available)
- Weight: 406 lbs. (184 kg)
- Dimensions: 67" (170.2 cm) H x 29" (73.7 cm) $W \times 29$ " (73.7 cm) D
- System comes ready to use.

DISTRIBUTED BY: